

PROTOPIC™ - 540 AUTO DUAL

PRINT ON DEMAND LAMINATOR

The Protopic™ - 540 Auto Dual will become the most versatile machine in your shop! The Protopic™ - 540 Auto Dual packs a formidable list of abilities, including single sided laminating, single sided SHR (Silver Halide Replacement), Spot Sleeking, and metallic foil fusing. With an integrated deep pile feeder for productivity, there is no other way to bring these value added processes in-house in a more economical and efficient package.



APPLICATIONS

- Single Side Lamination
- Single Sided SHR™ (Silver Halide Replacement)
- Whole Page Sleeking on Digital Media - Gloss, Matte and Holographic
- Spot Sleeking on Digital Media - Gloss, Matte, Holographic and Metallic

 49' per minute

 max. 21.25"W x 31.5"L

nobelus™
CONSIDER IT FINISHED

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Nobelus™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.

PROTOPIC™ - 540 AUTO DUAL


PRINT ON DEMAND LAMINATOR

KEY FEATURES



INTEGRATED DEEP PILE FEEDER

Automatic Deep Pile Feeder for ultimate productivity.



SHR™ EMBOSSING

SHR™ (Silver Halide Replacement) transforms digital prints with the rich texture of a silver halide print at a fraction of the cost. Eliminates toxic chemical processes.



CAPACITIVE TOUCH CONTROLLER

Intuitive Touch panel controller provides quick and easy access to all vital functions. The digital monitor screen displays settings and status messages.



SLEEKING TECHNOLOGY

Sleeking Technology opens a vast array of finishing options including variable data foil stamping, spot varnishing and holographic special effect sleeking on digital output.

Description	Specifications
Dimension	79"L x 31.5"W x 52"H
Maximum Laminating Speed	Single Sided Lamination: 50'/min Single Side SHR: 20'/min
Laminating Films	Nobelus Platinum™, Poly Pro™, NyPro™, and SHR™ OPP
Substrate Weight	120 ~ 300 g/m ³
Power Requirements	AC 220V ~ 240V, 50/60Hz
Power Consumption	3.45kw / 15A

Description	Specifications
Warm Up Time	15 Minutes
Heating System	Dual Infrared Heating Technology
Air Compressor	1HP, 0.6mPa, 89L/min
Laminating Temperature	Maximum 150°C (302°F)
Pressure Control	Pneumatic Cylinder
Film Core	3"
Cooling Device	DC Cooling Fan 5 set Top and Bottom Roller